

Viper 5W30 SN/CF

FULLY SYNTHETIC MOTOR OIL

It is a low viscosity, highly stable engine oil that is the result of the perfect blend of new generation additives and fully synthetic oils. It significantly prevents friction losses and deposit formation in the engine and provides resistance against wear. In addition to its excellent lubricating and anti-corrosion properties in a wide temperature range, it provides superior and long-lasting engine protection thanks to its formula developed with anti-wear technology. It is recommended for all kinds of high performance modern vehicles, passenger cars, gasoline engines with multi-point fuel injection, SUV and off-road vehicles.

TEST	METHOD	TYPICAL VALUES
KINEMATIC VISCOSITY (100°C), [MM ² /S = CST]	ASTM D445	9,3 - 12,5
VISCOSITY INDEX	ASTM D2270	Min. 155
FLASH POINT, °C	ASTM D92	Min. 200
POUR POINT, °C	ASTM D97	Max. -35

Approval and Specifications:

API SM / API SL, API CF, ACEA A3/B3/B4, MB-Approval 229.5, MB-Approval 229.3, Peugeot/Citroën B71 2296
Volkswagen VW50500, Volkswagen VW50200, Renault RN0710, Renault RN0700, BMW Longlife-01
Porsche A40, Opel GM-LL-B-025, Opel GM-LL-A-025, AVTOVAZ (LADA cars)

INFILUBE

MADENİ YAĞ SANAYİ VE TİCARET A.Ş.

Telefon : +90 216 361 68 48 Fax : +90 216 361 68 48

E-Posta : info@infilube.com

Adres: Girne Mah. Irmaklar Sk. Küçükyalı İş Merkezi

No:1-A 34852 - Maltepe / İstanbul