

Viper 5W40 SN/CF

FULLY SYNTHETIC MOTOR OIL

It has been especially developed to meet the requirements of modern high power automobiles.

The blend of synthetic oils with the latest additive technology has been developed to meet the full best performance expectations in low viscosity and high profitability engine oil. It reliably prevents deposit formation, reduces friction losses and protects against wear. Thus, it creates more powerful performance for modern, high performance and old engines. It is the new generation, most advanced engine oil that is produced especially for use in stop-and-go city traffic and provides long-lasting and superior engine protection.

TEST	METHOD	TYPICAL VALUES
KINEMATIC VISCOSITY (100°C), [MM ² /S = CST]	ASTM D445	12,5-16,3
VISCOSITY INDEX	ASTM D2270	Min. 155
FLASH POINT, °C	ASTM D92	Min. 210
POUR POINT, °C	ASTM D97	Max. -35

Approval and Specifications:

ACEA A3/B4;A3/B3, API SN/CF, MB 229.5/229.3/226.5, PORSCHE A40, PSA B71 2296 , RENAULT RN 0700; RN 0710, VW 502.00 ;VW 505.00

INFILUBE

MADENİ YAĞ SANAYİ VE TİCARET A.Ş.

Telefon : +90 216 361 68 48 Fax : +90 216 361 68 48

E-Posta : info@infilube.com

Adres: Girne Mah. Irmaklar Sk. Küçükalyalı İş Merkezi

No:1-A 34852 - Maltepe / İstanbul