

Viper 10W30 SL/CF

MOTOR OIL

10W/30 is synthetic engine oil that produces to respond the lubrication need of modern high speed and high efficiency turboc-charged engines by synthetic and high quality base oils and high-tech additives. It is used safely in all vehicles that work by gasoline, diesel and LPG, Provides fuel economy by excellent viscosity control property. Effective detergent and dispersant additives prevent deposit formation and keeps engine clean.

TEST	METHOD	TYPICAL VALUES
KINEMATIC VISCOSITY (100°C), [MM ² /S = CST]	ASTM D445	9,3 - 12,5
VISCOSITY INDEX	ASTM D2270	MIN. 115
FLASH POINT, °C	ASTM D92	MIN. 210
POUR POINT, °C	ASTM D97	Max. -36

Approval and Specifications:

API SL/CF, VW 501.01 / 505.00, ACEA A3/B3-04, MAN M 3277, MB APPROVAL 299,1

INFILUBE

MADENİ YAĞ SANAYİ VE TİCARET A.Ş.

Telefon : +90 216 361 68 48 Fax : +90 216 361 68 48

E-Posta : info@infilube.com

Adres: Girne Mah. Irmaklar Sk. Küçükyalı İş Merkezi

No:1-A 34852 - Maltepe / İstanbul