

Viper 20W50 SL/CF

MOTOR OIL

Viper 20W-50 is produced by blending quality base oils and high performance additives. It is gasoline engine oil. Especially with gasoline and LPG vehicles that are used extensively in urban traffic. It is an engine oil that can be used in all seasons with effective performance in passenger and commercial diesel engines. The detergent, dispersant and antifoam additives it contains keep the engine clean for a long time, it prevents the formation of sediment and deposits. It protects the oil film thickness by reducing the effect of heat change on oil viscosity. It facilitates the first start-up in cold weather and provides effective lubrication in hot weather. It protects the engine against all kinds of corrosion and rust and prolongs its life. With effective detergent and dispersant additives, it prevents the formation of deposits and keeps the engine clean. It provides fuel economy with its excellent viscosity control feature.

TEST	METHOD	TYPICAL VALUES
KINEMATIC VISCOSITY (100°C), [MM2/S = CST]	ASTM D445	16,3-21,9
VISCOSITY INDEX	ASTM D2270	MIN.110
FLASH POINT, °C	ASTM D92	MIN.230
POUR POINT, °C	ASTM D97	Max24

Approval and Specifications:

API SL/CF, VW 501.01 / 505.00, ACEA A3/B3-04, MB Approval 229.1

INFILUBE

MADENİ YAĞ SANAYİ VE TİCARET A.Ş.

Telefon: +90 216 361 68 48 Fax: +90 216 361 68 48

 $\hbox{E-Posta}: in fo@infilube.com$

Adres: Girne Mah. Irmaklar Sk. Küçükyalı İş Merkezi

No:1-A 34852 - Maltepe / İstanbul

