

Viper 15W40 CH-4

DIESEL MOTOR OIL

Viper 15W-40, advanced technology performance with well refined mineral base oil it is an all-season engine oil prepared with additive packages. In passenger and commercial vehicles, Europe and It is recommended for use in American designed, low emission, turbocharged engines. on highways working for both high speed/heavy load and light and heavy truck transportation working under heavy load in field conditions such as construction and agriculture. Also recommended for vehicles. It provides easier first start- up thanks to its superior fluidity at low temperatures. It provides fuel economy and long service life with its excellent viscosity control feature. Extends oil change intervals even when using high-sulphur fuel. With the new generation additives used, it ensures that the engine parts are kept cleaner. Protects the engine by prolonging its life.

TEST	METHOD	TYPICAL VALUES
KINEMATIC VISCOSITY (100°C), [MM ² /S = CST]	ASTM D445	12,5 - 16,3
VISCOSITY INDEX	ASTM D2270	MIN. 145
FLASH POINT, °C	ASTM D92	MIN. 225
POUR POINT, °C	ASTM D97	MAX. -32

Approval and Specifications:

API CH-4/CG-4/CF-4, API SL/SJ, ACEA E3/E5, MB 228.3, CUMMINS: CES 20077, 76, 75, 72, 71, MAN 3275, Volvo VDS- 2, RENAULT TURCKS: RD-2, MTU Level 2, Deutz DQC-I-05, MACK: EOM, EOM+, ALLISON: C-4

INFILUBE

MADENİ YAĞ SANAYİ VE TİCARET A.Ş.

Telefon : +90 216 361 68 48 Fax : +90 216 361 68 48

E-Posta : info@infilube.com

Adres: Girne Mah. Irmaklar Sk. Küçükyalı İş Merkezi

No:1-A 34852 - Maltepe / İstanbul