

Viper 15W40 CF-4

DIESEL MOTOR OIL

It is a diesel engine oil reinforced with high quality base oils and high additives. It is an engine oil that can be used safely in all seasons for automobiles and light commercial vehicles. It is especially suitable for passenger cars that work under difficult conditions and frequently stop and go. It can also be used safely in the lubrication of minibuses, vans, other four-stroke engines and other construction equipment. It can also be used safely in vehicles operating with fuels such as gasoline and LPG.

TEST	METHOD	TYPICAL VALUES
KINEMATIC VISCOSITY (100°C), [MM ² /S = CST]	ASTM D445	12,5 - 16,3
VISCOSITY INDEX	ASTM D2270	MIN. 145
FLASH POINT, °C	ASTM D92	MIN. 225
POUR POINT, °C	ASTM D97	MAX. -32

Approval and Specifications:

API CF-4/CF, API SJ/SL, ACEA B2, ACEA E3/E7, MB-Onay 228.3, VOLVO VDS-3 Cummins CES 20072, Mack EO-N, Mack EO-M, MAN M 3275-1, RENAULT TRUCKS RD-2, RENAULT TRUCKS RLD, Caterpillar ECF-2, Cummins CES 20077, Ford WSS-M2C171-D

INFILUBE

MADENİ YAĞ SANAYİ VE TİCARET A.Ş.

Telefon : +90 216 361 68 48 Fax : +90 216 361 68 48

E-Posta : info@infilube.com

Adres: Girne Mah. Irmaklar Sk. Küçükyalı İş Merkezi

No:1-A 34852 - Maltepe / İstanbul