

Viper ATV III

AUTOMATIC TRANSMISSION FLUID

Automatic transmission from Viper ATF III used as a GM DEXRON III fluid high performance that meets specification it is a synthetic technology product. Viper ATF III product for passenger cars and heavy automatic transmission and transmissions, steering gears, and with hydraulic system if recommended used in mechanisms. High performance level against wear. Requirements of commercial vehicles and passenger vehicles meets at the highest level. Rust and corrosion sensitive system prolongs the life of the components. Provides long transmission life and transmission increases efficiency. Prevents wear of automatic transmission parts. Compatible with all sealing elements. Does not become too thick at low temperatures and easy to transmit.

TEST	METHOD	TYPICAL VALUES
KINEMATIC VISCOSITY (100°C), [MM ² /S = CST]	ASTM D445	7,2 - 9,4
VISCOSITY INDEX	ASTM D2270	MIN. 130
FLASH POINT, °C	ASTM D92	MIN. 215
POUR POINT, °C	ASTM D97	Max. -36

Approval and Specifications:

ZF TE-ML 04D,14A (ZF001760),MAN 339 TYP Z1 AND V1,MB 236.6 , Voith 55.6336, ZF TE ML 14B,17C, ALLISON C-4,CAT TO-2,FORD MERCON AND MERCON V,GM DEXRON III H

INFILUBE

MADENİ YAĞ SANAYİ VE TİCARET A.Ş.

Telefon : +90 216 361 68 48 Fax : +90 216 361 68 48

E-Posta : info@infilube.com

Adres: Girne Mah. Irmaklar Sk. Küçükalyalı İş Merkezi

No:1-A 34852 - Maltepe / İstanbul