

Viper 75W90 GL-5

GEAR OIL

It is a synthetic gear oil formulated from synthetic base oils and advanced additive system to meet the performance requirements of harsh conditions. It is designed for heavy-duty manual transmissions and rear axles where extreme pressure shock loading is expected, with excellent load carrying capacity over a wide operating temperature range. This gear oil has excellent thermal and oxidation stability, high Viscosity Index, very low pour point and high fluidity at low temperature.

TEST	METHOD	TYPICAL VALUES
KINEMATIC VISCOSITY (100°C), [MM ² /S = CST]	ASTM D445	13,5 - 18,5
VISCOSITY INDEX	ASTM D2270	MIN. 140
FLASH POINT, °C	ASTM D92	MIN. 200
POUR POINT, °C	ASTM D97	MAX. -35

Approval and Specifications:

API GL-5/GL-4, MAN 342 M-1, MAN 342 M-2, ZF 05A/07A/08/12A/12E/16B-D/17B/19B/21A, SAE J2360, Volvo 1273.10, Scania STO 1:0, Industrial

INFILUBE

MADENİ YAĞ SANAYİ VE TİCARET A.Ş.

Telefon : +90 216 361 68 48 Fax : +90 216 361 68 48

E-Posta : info@infilube.com

Adres: Girne Mah. Irmaklar Sk. Küçükyalı İş Merkezi

No:1-A 34852 - Maltepe / İstanbul