

Viper 85W140 GL-5

GEAR OIL

Viper 85W140 GL-5 is a high-performance gear lubricant formulated from select base oils and an advanced additive system. Thanks to its special formula provides effective protection against corrosion may occur in severe operating conditions. Suitable for differentials and transaxles of vans, trucks, and buses when the manufacturer recommends a GL-5 transmission oil with a viscosity of SAE 85W-140. Shows very high extreme-pressure properties for optimal protection against scuffing. Increased protection against wear and tear, also under high stress working conditions. Have extreme pressure (EP) resistant to corrosion and oxidation and antifoaming properties. It is suitable in four seasons due to its multigrade properties.

TEST	METHOD	TYPICAL VALUES
KINEMATIC VISCOSITY (100°C), [MM ² /S = CST]	ASTM D445	MIN. 32,1
VISCOSITY INDEX	ASTM D2270	MIN. 99
FLASH POINT, °C	ASTM D92	MIN. 230
POUR POINT, °C	ASTM D97	MAX. -15

Approval and Specifications:

API GL-5/GL-4, ZF TE-ML 05A, 7A, 12E, 16B, C and D, 17B, 19B, 21B, MAN 342M-1, MAN 342 M-2, Scania STO 1:0, Volvo 1273.12, DIN 51517 Part 3, U.S. Steel 224, AGMA 9005-D94

INFILUBE

MADENİ YAĞ SANAYİ VE TİCARET A.Ş.

Telefon : +90 216 361 68 48 Fax : +90 216 361 68 48

E-Posta : info@infilube.com

Adres: Girne Mah. Irmaklar Sk. Küçükyalı İş Merkezi

No:1-A 34852 - Maltepe / İstanbul