

Viper 90 GL-4

GEAR OIL

It is a special gear oil formulated from mineral base oils obtained from modern refining processes and high quality additives. It has been developed for use in transmissions of automobiles and commercial vehicles. Its formula, developed using state-of-the-art additives, provides maximum protection against wear in the transmission. It has superior pumpability with its excellent fluidity at low temperatures. Thanks to its excellent oil film durability, it has superior lubricating properties. It is resistant to extreme pressure (EP), has anti-rust, oxidation and anti-foaming properties.

TEST	METHOD	TYPICAL VALUES
KINEMATIC VISCOSITY (100°C), [MM ² /S = CST]	ASTM D445	13,5 – 18,5
VISCOSITY INDEX	ASTM D2270	MIN. 99
FLASH POINT, °C	ASTM D92	MIN. 220
POUR POINT, °C	ASTM D97	MAX. -18

Approval and Specifications:

API GL-4, U.S. Steel 224, AGMA 9005-D94, David Brown S1.53.101(E), DIN 51517 Part 3, ZF TE-ML 02A, 08, 16A, 17A, 19A

INFILUBE

MADENİ YAĞ SANAYİ VE TİCARET A.Ş.

Telefon : +90 216 361 68 48 Fax : +90 216 361 68 48

E-Posta : info@infilube.com

Adres: Girne Mah. Irmaklar Sk. Küçükalyalı İş Merkezi

No:1-A 34852 - Maltepe / İstanbul