

Viper 140 GL-4

GEAR OIL

Is high performance, heavy duty gear lubricants formulated from high quality base oils and an advanced additive system. Have been developed to be used in gearboxes of passenger cars, on highway light and heavy duty trucks, and commercial vehicles. Prevents premature gear system failure due by maintaining viscosity longer. Protect gears from deposit buildup under the stress caused by hauling extra-heavy loads with our thermally durable additive system, which resists oxidation and deposits. Have extreme pressure (EP) resistant to corrosion and oxidation and antifoaming properties.

TEST	METHOD	TYPICAL VALUES
KINEMATIC VISCOSITY (100°C), [MM ² /S = CST]	ASTM D445	MIN. 32,1
VISCOSITY INDEX	ASTM D2270	MIN. 99
FLASH POINT, °C	ASTM D92	MIN. 230
POUR POINT, °C	ASTM D97	MAX. -15

Approval and Specifications:

API GL-4, U.S. Steel 224, AGMA 9005-D94, David Brown S1.53.101(E), DIN 51517 Part 3, ZF TE-ML 02A, 08, 16A, 17A, 19A

INFILUBE

MADENİ YAĞ SANAYİ VE TİCARET A.Ş.

Telefon : +90 216 361 68 48 Fax : +90 216 361 68 48

E-Posta : info@infilube.com

Adres: Girne Mah. Irmaklar Sk. Küçükalyalı İş Merkezi

No:1-A 34852 - Maltepe / İstanbul