

Viper 10W30 GL-4

TRACTOR OIL

Viper 10W30 GL-4 In manual or "Power-Shift", "Shuttle-Shift" and CVT automatic transmissions, front/rear axle and oil-bath brake systems (wet brake), final drive unit of tractors, agricultural and construction machinery that require the use of oil with especially high shear strength, It is a high performance (UTTO) transmission oil developed with the latest technology additive package and unique combination of special base oils for use in hydraulic and power steering systems.

TEST	METHOD	TYPICAL VALUES
KINEMATIC VISCOSITY (100°C), [MM ² /S = CST]	ASTM D445	9,5 - 12,5
VISCOSITY INDEX	ASTM D2270	MIN. 130
FLASH POINT, °C	ASTM D92	MIN. 210
POUR POINT, °C	ASTM D97	Max. -30

Approval and Specifications:

API GL-4 Meets API CF-4/SF MF - M1145 ZF TE-ML 06B(*), 07B MF M1139, MF M1144, JD J27, Ford M2C 159-B JD 20C, Ford M2C -134D and 86B, Case MS 1207 suitable for use in specified areas.

INFILUBE

MADENİ YAĞ SANAYİ VE TİCARET A.Ş.

Telefon : +90 216 361 68 48 Fax : +90 216 361 68 48

E-Posta : info@infilube.com

Adres: Girne Mah. Irmaklar Sk. Küçükyalı İş Merkezi

No:1-A 34852 - Maltepe / İstanbul