

Viper 5W40 CI-4/SL

FULLY SYNTHETIC MOTOR OIL

Viper 5W40 CI-4/SL It is a high performance fully synthetic heavy duty diesel engine oil that provides improved fuel economy and savings in maintenance costs thanks to its low viscosity feature. It can be used in diesel engines of heavy-duty construction machines, trucks, trucks and buses, including turbo and supercharged light commercial vehicles (minibuses, pickup trucks, etc.) and low-emission diesel engines that meet Euro V and Euro IV emission standards. It is suitable for use in all kinds of vehicles using fuels containing low or high amounts of sulfur and in all known high-speed diesel engines. It can be used safely in all seasons by providing constant lubrication in all kinds of climate and road conditions. It protects the engine against rust, oxidation, wear and foam formation. It increases the performance and with the help of detergent-dispersant additives it contains, it prevents the accumulation of residue by dispersing the dirt formed as a result of combustion in the environment. It provides fuel economy thanks to its low viscosity feature and improved viscosity stability. Saves on maintenance costs by meeting extended service interval requirements. Thanks to its improved viscosity stability, it provides excellent protection against wear even at the lowest ambient temperatures.

| TEST | METHOD | TYPICAL VALUES |
|---|------------|----------------|
| KINEMATIC VISCOSITY (100°C), [MM ² /S = CST] | ASTM D445 | 12,5-16,3 |
| VISCOSITY INDEX | ASTM D2270 | MIN. 150 |
| FLASH POINT, °C | ASTM D92 | MIN. 220 |
| POUR POINT, °C | ASTM D97 | Max. -36 |

Approval and Specifications:

API CI-4 ACEA E7, E4 CES 20078-77 DEUTZ DQC III-10 MTU TYPE 3 MACK EO-N, EO-M Plus MAN M 3277 MB 228.5

Renault RXD, RLD-2 Volvo VDS-3

INFILUBE

MADENİ YAĞ SANAYİ VE TİCARET A.Ş.

Telefon : +90 216 361 68 48 Fax : +90 216 361 68 48

E-Posta : info@infilube.com

Adres: Girne Mah. Irmaklar Sk. Küçükyalı İş Merkezi

No:1-A 34852 - Maltepe / İstanbul