

Viper ATV IV

MULTI AUTOMATIC TRANSMISSION FLUID

ATF Dexron 4+ is a synthetic automatic transmission fluid formulated with high performance synthetic base oils and advanced additive technology, meeting Dexron III and Dexron II performances as well as DEXRON IV. It provides excellent flow properties at low starting and high operating temperatures. Provides improved shift performance in Chrysler vehicles. It has good viscosity stability. Excellent oxidation stability enables less fluid usage in high temperature service. Protects against rust and corrosion. Provides more assured wear protection for maximum transmission/transmission life.

TEST	METHOD	TYPICAL VALUES
KINEMATIC VISCOSITY (100°C), [MM ² /S = CST]	ASTM D445	6,4 – 7,5
VISCOSITY INDEX	ASTM D2270	MIN. 145
FLASH POINT, °C	ASTM D92	MIN. 200
POUR POINT, °C	ASTM D97	Max. -38

Approval and Specifications:

JASO M315 1A-LV, MERCON LV, Acurat ATF-Z1, Aisin Warner JWS 3309 (T-IV) & JWS 3324 (WS), ATF RED 1, RED 1K, AUDI G 055 025 A2 (JWS 3309), BMW JWS 3309(T-IV), BMW Mini, Chrysler Dodge Mopar AS 68 RC (T-IV), JWS 3309, Daihatsu AMMIX ATF D-II, Daihatsu AMMIX ATF D-III SP, FIAT T-IV type, JWS 3309, Ford FNRS, Ford WSS M2C 922A1, 924A (XT-8- QAW) JWS 3309, FUSO ATF-II, FUSO ATF – SP III, FUSO ATF A4, GM 9986195 (Aisin AW, JWS 3309), HINO Blue Ribbon ATF, Honda ATF-Z1 (except in CVTs), Honda DW 1, Hyundai/Kia SP-III, Hyundai/Kia SP IV, Hyundai/Kia SP IV M, Hyundai/Kia SP IV RR, Hyundai/Kia JWS 3314, Hyundai/Kia JWS 9683, ISUZU BESCO ATF-II, ATF-III, JASO M315-2013 1A, JASO M315- 2013 1A-LV, JASO M315-2013 2A, Lexus JWS 3309, KIA ATF SP II, SP III, SP IV, SP IVM, Red 1, MAZDA ATF D II, MAZDA ATF M III, Mazda ATF M-V, Mazda ATF FZ, Mazda ATF S- 1, Mazda ATF N-1, Mazda ATF 3317, MINI COOPER T-IV, Mitsubishi, Diaqueen SK, itsubishi, Diaqueen SP II, Mitsubishi, Diaqueen SP, III Mitsubishi Diaqueen SP IV, Mitsubishi Diaqueen AW, Mitsubishi Diaqueen J2, Mitsubishi Diaqueen J3, Mitsubishi Diaqueen ATF PA, Nissan Matic Fluid C, D, J, K and S, Porsche T-IV (JWS 3309), Saab T-IV (JWS 3309), Saab 93 165 147, Saturn T-IV (JWS 3309), Scion (all vehicles), Subaru ATF, ATF 5AT, ATF HP, Subaru Dexron®-II, Suzuki ATF 3314, Suzuki AT OIL 5D06, Suzuki ATF 2326, Suzuki ATF 2384K, Suzuki ATF JWS 3309, Suzuki ATF 3317, Texaco N402, Toyota ATF T-III, T-IV, Toyota ATF D-II, D-III, Toyota ATF WS, Ford MERCON, Ford MERCON LV (FF-WSS- M2C-938A/SF, XT-10 QLV), Mazda ATF F-1

INFILUBE

MADENİ YAĞ SANAYİ VE TİCARET A.Ş.

Telefon : +90 216 361 68 48 Fax : +90 216 361 68 48

E-Posta : info@infilube.com

Adres: Girne Mah. Irmaklar Sk. Küçükyalı İş Merkezi

No:1-A 34852 - Maltepe / İstanbul